



# MATERIAL SAFETY DATA SHEET

## WYNN'S 100% SYNTHETIC SAE 10W50 API SL MOTOR OIL

WYNN'S  
A division of Illinois Tool Works Inc.  
1151 West Fifth Street  
Azusa, California 91702

**EMERGENCY TELEPHONE NUMBER:**  
Chemtrec (800) 424-9300  
**INFORMATION TELEPHONE NUMBER:**  
Wynn's (626) 334-0231

### PRODUCT IDENTIFICATION

PRODUCT NAME	EFFECTIVE DATE	PRODUCT CODE
Wynn's 100% Synthetic SAE 10W50 API SL Motor Oil	10-28-05	42601, 42602, 42603
CHEMICAL NAME	CAS NUMBER	
N/A	N/A	

### HAZARDOUS INGREDIENTS

COMMON NAME	CHEMICAL NAME	CAS NO.	%	OSHA PEL	ACGIH TLV-TWA
Petroleum Hydrocarbon	Petroleum Oil (UCBO)	64742-54-7	<90%	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>

Contains no other ingredients now known to be hazardous as defined by OSHA 29CFR 1910.1000(z) and 29CFR 1910.1200.

### PHYSICAL DATA

These data are approximate or typical values and should not be used as precise specifications. Unless otherwise noted values are at 20°C(68°F) and 760 mmHg (1 atm).

<b>Boiling Point/Range</b>	>572EF(>300EC)	<b>Freeze Point</b>	N/A
<b>Specific Gravity (H<sub>2</sub>O=1) @ 15.6°C</b>	0.853	<b>Vapor Pressure (mm Hg)</b>	<0.01
<b>Vapor Density (Air =1)</b>	Heavier than air	<b>Solubility in Water (%)</b>	0
<b>% Volatiles by Volume</b>	0	<b>Evaporation Rate (Butyl Acetate = 1)</b>	Slower than ether
<b>pH (as is)</b>	N/A	<b>pH (dilute) @ %</b>	N/A
<b>Appearance</b>	Brown, Oily Liquid	<b>Odor</b>	Petroleum

N/D - Not Determined

N/A - Not Applicable

< = Less Than

> = Greater Than

---

## FIRE AND EXPLOSION HAZARD DATA

---

**Flash Point** >392°F(200 °C) **Method** Cleveland Open Cup ASTM D-92

**Flammable or Explosive Limits** (Approximate percent by volume in air)

Lower (LEL) N/D

Upper (UEL) N/D

**Hazard Class Identification**

	<b>Flammability</b> 1		<b>Hazard Code</b> 0 - Least (insignificant)
<b>Health</b> 1		<b>Reactivity</b> 0	1 - Slight
	<b>Other</b> --		2 - Moderate
			3 - High
			4 - Extreme

**Extinguishing Media**

Dry chemicals, water fog, foam, carbon dioxide.

**Special Fire Fighting Procedures**

Use water to cool fire-exposed containers. Fire fighters use a self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards**

Combustion will produce smoke and toxic fumes.

---

## REACTIVITY DATA

---

**Stability**

Stable.

**Conditions to Avoid**

Heat, open flame.

**Materials to Avoid**

Strong oxidizing agents.

**Hazardous Decomposition or Combustion Products**

Thermal decomposition may produce carbon monoxide and asphyxiants.

**Hazardous Polymerization (conditions)**

Will not occur.

---

## HEALTH HAZARDS/ROUTES OF ENTRY

---

### Signs, Symptoms and Effects of Overexposure

**Ingestion** (swallowing) DO NOT swallow. If swallowed, may cause irritation to digestive tract.

**Skin Contact** May cause irritation to skin in very sensitive individuals.

**Eye Contact** May cause irritation to the eyes on direct contact.

**Inhalation** (breathing) Vapors generated at elevated temperatures can cause irritation to respiratory tract.

### Other Effects of Prolonged/Repeated Overexposure

This material has not been identified as a carcinogen by NTP, IARC or OSHA. Prolonged and repeated contact with skin may cause mild skin irritation and inflammation.

---

## EMERGENCY AND FIRST AID PROCEDURES

---

**Ingestion** (swallowing) DO NOT induce vomiting. Call for medical help.

**Skin Contact** Wash affected area with soap and water. If irritation persists, call for medical help.

**Eye Contact** Flush with water for 15 minutes. If irritation persists, call for medical help.

**Inhalation** (breathing) Remove to fresh air to avoid further inhalation.

---

## SPILL OR RELEASE CONTROL PROCEDURES

---

### Steps to be taken in case material is released or spilled

Use absorbent sand, clay or vermiculite. Shovel into containers. Prevent liquid from entering into sewers and waterways.

### Waste Disposal Method

Dispose of in accordance with Federal, State and Local regulations.

**EPA Reportable Quantity (RQ)**, 40CFR302 (CERCLA104)

N/A

**EPA Toxic Chemical Release Reporting, 40CFR372(SARA313)**

<b>Chemical</b>	<b>CAS NO.</b>	<b>% in Product</b>
N/A	N/A	N/A

---

## **HANDLING AND STORAGE**

---

### **Handling and Storage Precautions**

CAUTION: Contains petroleum oil. Avoid skin and eye contact. DO NOT store opened containers. Use entire contents. Combustible. Keep away from heat or flame.

### **Other Precautions**

KEEP AWAY FROM CHILDREN.

---

## **PERSONAL PROTECTION - EXPOSURE CONTROL**

---

### **Ventilation**

Normal use, none required. If misting occurs, a mechanical or local exhaust is recommended.

### **Respiratory Protection**

Normal use, none required.

### **Eye Protection**

Safety glasses.

### **Protective Gloves**

Rubber, plastic gloves.

### **Other Protective Clothing or Equipment**

None special.

### **Work/Hygienic Practices**

Personal cleanliness is always appropriate. Frequent washing minimizes chances of inadvertent exposure.

---

## TRANSPORTATION INFORMATION

---

**Department of Transportation (DOT) Classification**

	Flammable Liquid		Corrosive
	Flammable Solid		Non-Flammable Gas
	Flammable Gas	XXX	Not Hazardous by DOT
	Combustible Liquid		Other:

**DOT Proper Shipping Name**

N/A

**DOT ID Number**

N/A

---

## DOCUMENTATION

---

Product Code No.: 42601, 42602, 42603  
Previous Code No.: 42601, 42602, 42603

Issue Date: 10-28-05  
Prior Date: 07-02-02

This information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.