



MATERIAL SAFETY DATA SHEET

WYNN'S PROFESSIONAL PRODUCTS

OIL SYSTEM CLEANER & CONDITIONER

WYNN'S
A division of Illinois Tool Works Inc.
1151 West Fifth Street
Azusa, California 91702

EMERGENCY TELEPHONE NUMBER:
Chemtrec (800) 424-9300
INFORMATION TELEPHONE NUMBER:
Wynn's (626) 334-0231

PRODUCT IDENTIFICATION

| PRODUCT NAME | EFFECTIVE DATE | PRODUCT CODE |
|--|----------------|-------------------------------|
| Wynn's Professional Products Oil System Cleaner & Conditioner | 08-30-05 | 61603, 61607, 61610, 61614 |
| CHEMICAL NAME | CAS NUMBER | |
| N/A | N/A | |

HAZARDOUS INGREDIENTS

| COMMON NAME | CHEMICAL NAME | CAS NO. | OSHA PEL | ACGIH TLV-TWA |
|-----------------------|----------------------|------------|-----------------|-----------------|
| Petroleum Hydrocarbon | Petroleum Distillate | 68476-34-6 | Not Established | Not Established |
| Petroleum Hydrocarbon | Petroleum Distillate | 64741-97-5 | Not Established | Not Established |

Contains no other ingredients now known to be hazardous as defined by OSHA 29CFR 1910.1000(z) and 29CFR 1910.1200.

PHYSICAL DATA

These data are approximate or typical values and should not be used as precise specifications. Unless otherwise noted values are at 20°C(68°F) and 760 mmHg (1 atm).

| | | | |
|---|----------------------------|---|-----------------|
| Boiling Point/Range | 325-700°F (162.8-371°C) | Freeze Point | -25°F(-31.67°C) |
| Specific Gravity (H₂O=1) @ 15.6°C | 0.86 | Vapor Pressure (mm Hg) | N/D |
| Vapor Density (Air =1) | Heavier Than Air | Solubility in Water (%) | Disperses |
| % Volatiles by Volume | N/D | Evaporation Rate (Butyl Acetate = 1) | N/D |
| pH (as is) | N/A | pH (dilute) @ % | N/A |
| Appearance | Clear Brown Thin Liquid | Odor | Hydrocarbon |

N/D - Not Determined

N/A - Not Applicable

< = Less Than

> = Greater Than

FIRE AND EXPLOSION HAZARD DATA

Flash Point 175°F(79°C) **Method** Pensky - Martens Closed Cup ASTM D-93

Flammable or Explosive Limits (Approximate percent by volume in air)

Lower (LEL) N/D Upper (UEL) N/D

Hazard Class Identification

| | | | |
|--------------------|--------------------------|------------------------|---|
| | Flammability 2 | | Hazard Code 0 - Least (insignificant) 1 - Slight 2 - Moderate 3 - High 4 - Extreme |
| Health 2 | | Reactivity 0 | |
| | Other -- | | |

Extinguishing Media

Dry chemicals, carbon dioxide, water spray, foam.

Special Fire Fighting Procedures

Use water only to cool fire exposed containers. Fire fighters wear a self contained breathing apparatus.

Unusual Fire and Explosion Hazards

The material is combustible and may be ignited by heat or flame.

REACTIVITY DATA

Stability

Stable.

Conditions to Avoid

Heat, open flame.

Materials to Avoid

Strong oxidizing agents.

Hazardous Decomposition or Combustion Products

Thermal decomposition may produce oxides of carbon, nitrogen, phosphorus, and zinc.

Hazardous Polymerization (conditions)

Will not occur.

HEALTH HAZARDS/ROUTES OF ENTRY

Signs, Symptoms and Effects of Overexposure

Ingestion (swallowing) May be harmful or fatal if swallowed. Due to its low viscosity, it may enter lungs during swallowing or vomiting. Once in lungs serious damage may occur.

Skin Contact Can be absorbed through skin on prolonged contact. Single contact, no effect likely. Prolonged and repeated contact can result in defatting and drying of the skin. Can cause redness and itching.

Eye Contact May cause irritation, burning, blurred vision and redness.

Inhalation (breathing) Inhalation can cause irritation to nose and throat and upper respiratory tract. Concentrated vapor respiration can cause dizziness, nausea and central nervous system damage.

Other Effects of Prolonged/Repeated Overexposure

This material has not been identified as a carcinogen by NTP, IARC or OSHA. Kidney damage may occur if large quantities are swallowed.

EMERGENCY AND FIRST AID PROCEDURES

Ingestion (swallowing) DO NOT induce vomiting. Call for medical help.

Skin Contact Remove contaminated clothing. Wash affected area with soap and water. Call for medical help.

Eye Contact Flush eyes with water for 15 minutes. If irritation persists call for medical help.

Inhalation (breathing) Remove person to fresh air to avoid further inhalation. Call for medical help.

Comments NOTE TO PHYSICIANS: If more than 2 ml per kg body weight has been ingested and vomiting has not occurred, emesis should be induced with medical supervision.

SPILL OR RELEASE CONTROL PROCEDURES

Steps to be taken in case material is released or spilled

Isolate area and restrict entry. Combustible. Eliminate ignition sources. Use absorbent sand or clay. Shovel in containers and remove out of doors. Prevent liquid from entering sewers and water ways.

Waste Disposal Method

In accordance with all Federal, State and Local regulations.

Environmental Hazard (EPA-CWA, Section 311)

Spills of this material to surface waters where it will cause a sheen must be reported to the National Response Center, (800) 424-8802.

EPA Reportable Quantity (RQ), 40CFR302 (CERCLA104)

N/A

EPA Toxic Chemical Release Reporting, 40CFR372(SARA313)

| Chemical | CAS NO. | % in Product |
|---------------|---------|--------------|
| Zinc Compound | -- | 1.75 |

HANDLING AND STORAGE

Handling and Storage Precautions

WARNING: Contains petroleum distillates. Avoid skin and eye contact. Avoid breathing of vapors. Combustible. Keep away from heat and sparks. Use entire contents. DO NOT store opened containers.

Other Precautions

KEEP AWAY FROM CHILDREN.

PERSONAL PROTECTION - EXPOSURE CONTROL

Ventilation

Provide adequate general or local ventilation to maintain concentrations below TLV/PEL limits.

Respiratory Protection

None normally required. If vapors exceed TLV/PEL values, use a NIOSH approved respirator

Eye Protection

Safety glasses with side-shields.

Protective Gloves

Chemical-resistant gloves.

